



















# מדריך לבחירת גלגלים

## משקל כנף

מערכות	משקל כנף					
	ט"ב 30 ק"ג	ט"ב 80 ק"ג	ט"ב 120 ק"ג	ט"ב 180 ק"ג	ט"ב 200 ק"ג	ט"ב 320 ק"ג
<b>K7300</b> <b>K7500</b>	 מק"ט: T90092.30	 מק"ט: T90092.80	 מק"ט: T90092	 מק"ט: T90092.180		
<b>N22</b> <b>B22</b>	 מק"ט: T90092.30	 מק"ט: T90092.80	 מק"ט: T90092	 מק"ט: T90092.180		
<b>K9000</b>		 מק"ט: T90094.80		 מק"ט: T90094.180		 מק"ט: T90091.320 * לפי הזמנה
<b>W92</b> <b>K9200</b> <b>U22</b>		 מק"ט: T90094.80		 מק"ט: T90094.180		 מק"ט: T90091.320 * לפי הזמנה
<b>K2200</b> 4611					 מק"ט: T9550.200	
<b>K2200</b> 4609			 מק"ט: T90091.120			
<b>B22H</b>				 מק"ט: 6675.1		
<b>K9400</b>						 מק"ט: T90091.320 * לפי הזמנה

ניתן להגדיל עומס גלגלים לפי דרישת הלקוח והתאמה לפרויקט

Durability test: Performed in round-trip sliding movements over a distance of 800 mm for a total of 25,000 cycles at a speed of 4 cycles / min  
Polismar products are developed according to processes and procedures implemented by the quality management system according to ISO 9001: 2015